

# B-Track | K2x

## Rugged Duty Actuator DC Motor Ball Screw

Up to 2,200 lbs. Rated Load

Up to 2.7 in./sec. Travel Speed



The K2x model provides the highest load rating in its class. This model incorporates all of the base K2 features with a ball nut screw for a 2,200 lb. load capability within a compact package size. The K2x includes a bi-directional wrap spring brake for load holding capability. These units are well suited for the most demanding applications where an alternative to hydraulic or air cylinders is needed or where hydraulic power sources are not available.

Combining the K2x actuator with BTc control functionality results in precision actuator control at a fraction of the cost of more complicated servo actuator systems. See Controls Section for more information on BTc controls.

### Features

- Protective coatings and O-ring seals throughout
- Efficient in-line ball screw system
- Integral load holding brake
- Ball detent overload clutch
- 2 to 24 inch stroke lengths
- Up to 2,200 pound load capacities
- Speeds up to 2.7 in./sec. travel
- Thermal overload incorporated into the motor
- Heavy wall construction
- Double ball bearing motors and heat treated gears
- Rugged extension rod bearing support
- Optional 90 vdc motor for use with SBC-AC control
- Custom mounting options available

### Typical Applications

- Paving equipment
- Deck and implement lifts for tractors and mobile applications
- Spray booms
- Scissor and dump box lifts

### Load/Current/Speed/Duty Cycle

- Maximum Static Rating: 3000 lbs. Static (in-line load)
- Refer to performance chart for load/current/speed capabilities
- Stroke Length Tolerance: +/- .06"
- Motor is protected with auto reset breaker inside motor housing (temperature/current/time dependent)
- Overload clutch setting: +25% over rated dynamic load
- Duty cycle is time/temperature/load dependent, suggested guidelines are:
  - 50% max on-time/50% off-time for loads up to 50% of capability
  - 25% max on-time/75% off-time for loads between 50%-80% of capability
  - 10% max on-time/90% off-time for loads between 80%-100% of capability

(Load/stroke profiles will allow some adjustment variation from these guidelines.)

### Operating Environment

- Ambient temp range: -30°F to 150°F
- Weather resistant enclosure & seals (IP 65 capable, 250 hour salt spray, 500 hour for paint)
- Normal operating voltage: 10-16 vdc (Ratings are at 12 vdc Normal.)

### Control/Connections

- 14 gauge stranded lead wires-UL style 1230 w/PVC insulation Class F 105°C
- Lead wires abrasion protected with braided covering
- Use momentary contact double pole/double throw switch in powering unit for extend/retract operation. (ON)-OFF-(ON) DPDT
- Connectors:
  - Packard 56 series or Delphi Weather-Pack
  - Packard 56 series with 56 series blades (#2984883 & #2962987)
  - Delphi Weather-Pack series (#121015792 & #12010973)

